



Dust control options available

The smallest in the TFP range of scarifiers the TFP200 is perfect for small to medium jobs.

The rigid steel chassis ensures a strong, stable machine suitable for accurate surface preparation of concrete and steel surfaces, removing coatings, levelling and texturing.

The TFP200 is also our most popular machine for equipment hire fleets, a versatile range of power options together with simple operation and maintenance makes it the machine of choice for a demanding industry.

### **FEATURES**

- · 200mm cutting width
- Easy to use, maintain and manoeuvre
- Precise screw type cutter height adjustment for accurate removal and milling
- Angled dust port allows connection of industrial dust collector giving virtually dust free performance
- Choice of electric, petrol and pneumatic power sources for operation in a wide range of applications
- Rear mounted electrical switchgear utilizing vibration resistant components
- Customizable Heavy Duty Vinyl wrap

# **APPLICATIONS**

- Suitable when manoeuvrability is important
- Removal of hard coatings
- Levelling and removing layers of hard materials such as concrete
- Removing painted lines
- Grooving and texturing concrete
- Removal of coatings and scale from steel surfaces

## **KEY CONSUMABLES & ACCESSORIES**

lmage	Part Number	Description
0	320.5500	Tungsten Carbide Tipped Cutters For all concrete texturing, scabbling, planing and grooving applications
	320.4140	Spacers Used to create a gap in between cutters 88 required per TCT drum 196 required per grooving drum 72 required per milling drum
	320.3658	Star Cutters For the removal of paint, coatings and laitance. Deck descaling
**	320.5120	Beam Cutters For the removal of paint, coatings, laitance, grease, dirt and ice deposits. Deck descaling
	320.5600	Milling Cutters For the removal of thermoplastic road and runway markings, bituminous and rubber deposits.
	320.9620	Wire Brush For general cleaning and removal of light surface rust.

## **TECHNICAL DATA**

Model		Weight (Kg)			Cycle (Hz)	Cutter Speed (RPM)	Plug Size	Transformer Size	Recommended Cable Size (CSA)				Vibration Level (Aeq m/s2)
TFP200 Petrol	320.2400T	64	5.5 - 4.1	-	-	1833	-	-	-	-	Honda GX160	-	6.9
TFP200 110v TCT 50Hz	320.2402T	71	3 - 2.2	110	50	1650	32Amp	3 Kva*	4mm	20m	-	-	4.4
TFP200 230v TCT	320.2404T	71	3 - 2.2	230	50 / 60	1650	16Amp	-	4mm	40m	-	-	4.4
TFP200 400v TCT	320.2406T	71	3 - 2.2	400	50 / 60	1650	16Amp	-	4mm	40m	-	-	4.4
TFP200 110v TCT 60Hz	320.2416T	71	3 - 2.2	110	60	1650	32Amp	3 Kva*	4mm	20m	-	-	4.4
TFP200 Air TCT	320.2412T	62	3.5 - 2.6	-	-	1528	-	-	-	-	-	78lps - 165cfm	4.4

# **DIMENSIONS**

Working Width	Length		Height	Maximum Cutting	Working Distance from	Vacuum Take Off
(mm)	(mm)		(mm)	Depth (mm)	Wall (mm)	Diameter (mm)
200	900	350	900	3	55	50

- Trelawny recommends the use of a minimum 5 Kva continuous rated centre tap transformer with their 110v machines. All part numbers specified above are for machines complete with 5 point tungsten carbide tipped (TCT) cutters.
- For machines requiring alternative cutting media please specify.



+966 -11 - 21 40 888 marketing@aemco-llc.com www.aemco-llc.com

جده الدمام الرياض Riyadh Dammam Jeddah




Genuine People **Genuine Spares** Genuine Service









#### **ABOUT AEMCO**

AEMCO was established in 2007 as an organization focused to increase professionalism and productivity in the arena of coating and surface preparation across the Kingdom of Saudi Arabia. Latest trends and technologies in coating industry were made available from AEMCO to our professional end users to achieve quality results and satisfaction. We started our operations in Riyadh and expanded to Central, Eastern, Western and Northern Region of the Kingdom.

تأسست شركة إيمكو في عام ٢٠٠٧ لتكون شركة تركز على زيادة الاحترافية والإنتاجية في ميدان الطلاء وتجهيز الأسطح للدهان في المملكة العربية السعودية. وفرت شركة إيمكو أحدث أساليب التقنية في مجال تنفيذ الطلاء لعملائنا المحترفين في صناعة تنفيذ الطلاء للوصول الى نتائج مبهرة ومرضية. بدأنا عملياتنا في الرياض وتطورت لتصل الى المنطقة الوسطى، المنطقة الشرقية، المنطقة الغربية والمنطقة الشمالية من المملكة العربية السعودية.

#### **AEMCO LOCATIONS**

RIYADH	DAMMAM	JEDDAH
Second Ring Road,	King Abdul Aziz Road,	Prince Abdul Majeed
Near Morni,	Opp.DHL Head Office,	Road, North Obhur.
As Sulay,	Thuqba Area ,	Al Shera'a District,
Riyadh:14285, KSA	Al-Khobar KSA.	Jeddah: 23814, KSA
Tel: +966 11 2140888	Tel: +966 13 8021334	Tel: +966 11 2637048

All written and visual data contained in this document is based on the latest product information available at the time of publication. AEMCO reserves the right to make changes at any time without notice



+966 -11- 21 40 888 marketing@aemco-llc.com www.aemco-llc.com جده الدمام الرياض

Riyadh Dammam Jeddah



Genuine People Genuine Spares Genuine Service