

HERO

INNOVATIVE COLOR TECHNOLOGY

- FUSION STD •
S2850M
Manual Clamp Automatic Gyroscopic Mixer

AEMCO

+966 -11- 21 40 888
marketing@aemco-llc.com
www.aemco-llc.com

جده الدمام الرياض
Riyadh Dammam Jeddah



Genuine People
Genuine Spares
Genuine Service



• FUSION STD •
S2850M

Manual Clamp Automatic Gyroscopic Mixer

The S2850M Fusion STD is HERO's latest addition to its paint mixer family. The S2850M is specifically designed for use with hard to mix highly viscous paints. A simple and durable mixer with great ergonomics and ease of use. The Fusion STD is equipped with a front load roller which makes the unit easy to load. It also comes with a slotted rubber bottom plate for easy can centering and solid container support. This unit is also available in a roller-line configuration with metal bottom plate and built in bail handle support.





● ● ● ADVANTAGES:

- Unbeatable robustness and durability
- Simplicity in the design and in the electronics
- Low number of components
- Low maintenance required
- Built in cycle counter located on internal board

● ● ● PROBLEMS SOLVED:

- Reinforced sliding door for easy access and improved durability
- Unique paint spill containment system with spill catch and drain spout for easy cleanup
- Improved built in voltage fluctuation protection

● ● ● ERGONOMICS AND EASE OF USE:

- Door safety lock - unit will not operate when door is open. Door cannot not be opened while the unit is running
- Front roller make the unit easy to load
- Emergency stop - cuts power to the motor immediately
- Equipped with 3 wheels for easy installation and setup
- 4 leveling feet allow for can load height adjustment to standard roller lines



• • • Technical features

Maximum can height:	400mm
Maximum clamping clearance:	407mm
Minimum can height:	70 mm (185 mm with pail holder installed)
Maximum can diameter:	340mm
Can clamping:	manual
Can holder assembly lock:	yes - top dead center
Door:	plastic shutter with metal bars for safety
Emergency switch:	yes
Door safety lock:	yes
Timer:	mechanical (up to 6 min)
Rotation direction [viewed from front]:	counter-clockwise
Main motor:	1 Hp. 1425 rpm (230 V) or 1725 rpm (115 V)
Speed ratio - can holder ass'y:	bottom plate 1 : 2
Stirring velocity:	single speed - all cans, can holder ass'y - 100 rpm (nominal), can spin - 200 rpm (nominal)
Maximum noise level:	55 db
Machine Dimensions:	l 900 x d 810 x h 1210 mm
Weight:	200 Kg
Shipping Dimensions:	l 950 x d 850 x h 1375 mm
Gross Weight:	235 Kg

ABOUT AEMCO

AEMCO was established in 2007 as an organization focused to increase professionalism and productivity in the arena of coating and surface preparation across the Kingdom of Saudi Arabia. Latest trends and technologies in coating industry were made available from AEMCO to our professional end users to achieve quality results and satisfaction. We started our operations in Riyadh and expanded to Central, Eastern, Western and Northern Region of the Kingdom.

نبذة عن الشركة:

تأسست شركة إيمكو في عام ٢٠٠٧ لتكون شركة تركز على زيادة الاحترافية والإنتاجية في ميدان الطلاء وتجهيز الأسطح للدهان في المملكة العربية السعودية. وفرت شركة إيمكو أحدث أساليب التقنية في مجال تنفيذ الطلاء لعملائنا المحترفين في صناعة تنفيذ الطلاء للوصول الى نتائج مبهرة ومرضية. بدأنا عملياتنا في الرياض وتطورت لتصل الى المنطقة الوسطى، المنطقة الشرقية، المنطقة الغربية والمنطقة الشمالية من المملكة العربية السعودية.

AEMCO LOCATIONS

RIYADH	DAMMAM	JEDDAH
Second Ring Road, Near Morni, As Sulay, Riyadh:14285, KSA Tel: +966 11 2140888	King Abdul Aziz Road, Opp.DHL Head Office, Thuqba Area , Al-Khobar KSA. Tel: +966 13 8021334	Prince Abdul Majeed Road, North Obhur. Al Shera'a District, Jeddah: 23814, KSA Tel: +966 11 2637048

All written and visual data contained in this document is based on the latest product information available at the time of publication.
AEMCO reserves the right to make changes at any time without notice

AEMCO

+966 -11- 21 40 888
marketing@aemco-llc.com
www.aemco-llc.com

جده الدمام الرياض
Riyadh Damman Jeddah



Genuine People
Genuine Spares
Genuine Service