

COMPACTCUT 900

LISSMAC
CONSTRUCTION TECHNOLOGY

POWERFUL AND COMPACT FLOOR SAW FOR
CHALLENGING BUILDING SITE CONDITIONS

- Compact floor saw with scissor technology
- Saw blade drive can be switched off mechanically – safe moving and set up of the machine
- Drive via hydrostat guarantees smooth and controlled operation of the machine
- Optimum power transfer with high performance V-belts
- Warp-resistant sheet frame construction
- The compact design and balanced chassis permit easy manoeuvring around the construction site
- The low centre of gravity ensures a precise saw cut
- Very good straight cut thanks to the adjustable rear axle
- Electro- hydraulic lowering and raising of the saw blade with a threaded spindle with cutting depth indicator prevents damage to the saw blade
- Height adjustable handles for ergonomic operation
- Saw hood front can be raised for intersections
- Rapid changeover from left to right-hand cutting
- Easy access for prevalent maintenances (air filter, battery, oil filter, fuel filter) due to the perfect drive unit position
- Parking brake and neutral (free-wheeling) comes as a standard feature



COMPACTCUT 900 D



[1] Blade guard



[2] Spot-light



[3] Warning flasher



Operator panel

AEMCO

+966 -11- 21 40 888
marketing@aemco-llc.com
www.aemco-llc.com

جده الدمام الرياض
Riyadh Dammam Jeddah



Genuine People
Genuine Spares
Genuine Service

TECHNICAL DATA	COMPACTCUT 900 P	COMPACTCUT 900 D
cutting depth max.	320 mm	320 mm
cutting depth setting	electrohydr. with depth gauge	electrohydraulic with depth gauge
saw blade Ø max.	800 mm	800 mm
saw blade holder	25.4 mm	25.4 mm
drive motor	Briggs+Stratton petrol 2 cyl.	DEUTZ diesel 2 cylinder
output power max.	26.1 kW, 35 hp	22.3 kW, 30 hp
emission level	-	EU IIIA / US T3
saw blade speed	1750 1/min.	1650 1/min.
left and right cut	yes	yes
dimensions (L/W/H)	1370/820/1120 mm	1370/820/1120 mm
weight	539 kg	657 kg

DIAMOND TOOLS RECOMMENDATION

Asphalt	ASP 401
Concrete	BSP 301

FLOOR SAWS	NR.
COMPACTCUT 900 P without diamond blade, incl. blade guard 800 mm	1017763
COMPACTCUT 900 D without diamond blade, incl. blade guard 800 mm	1017762

ACCESSORIES	NR.
[1] COMPACTCUT 900 - blade guard 500 mm	816125
[1] COMPACTCUT 900 - blade guard 800 mm	816051
[2] COMPACTCUT 900 - spot-light LED 12 V	1040256
[3] COMPACTCUT 900 - warning flasher	816002
COMPACTCUT 900 - water pump set	813046

ABOUT AEMCO

AEMCO was established in 2007 as an organization focused to increase professionalism and productivity in the arena of coating and surface preparation across the Kingdom of Saudi Arabia. Latest trends and technologies in coating industry were made available from AEMCO to our professional end users to achieve quality results and satisfaction. We started our operations in Riyadh and expanded to Central, Eastern, Western and Northern Region of the Kingdom.

نبذة عن الشركة:

تأسست شركة إيمكو في عام ٢٠٠٧ لتكون شركة تركز على زيادة الاحترافية والإنتاجية في ميدان الطلاء وتجهيز الأسطح للدهان في المملكة العربية السعودية. وفرت شركة إيمكو أحدث أساليب التقنية في مجال تنفيذ الطلاء لعملائنا المحترفين في صناعة تنفيذ الطلاء للوصول الى نتائج مبهرة ومرضية. بدأنا عملياتنا في الرياض وتطورت لتصل الى المنطقة الوسطى، المنطقة الشرقية، المنطقة الغربية والمنطقة الشمالية من المملكة العربية السعودية.

AEMCO LOCATIONS

RIYADH	DAMMAM	JEDDAH
Second Ring Road, Near Morni, As Sulay, Riyadh:14285, KSA Tel: +966 11 2140888	King Abdul Aziz Road, Opp.DHL Head Office, Thuqba Area , Al-Khobar KSA. Tel: +966 13 8021334	Prince Abdul Majeed Road, North Obhur. Al Shera'a District, Jeddah: 23814, KSA Tel: +966 11 2637048

All written and visual data contained in this document is based on the latest product information available at the time of publication.
AEMCO reserves the right to make changes at any time without notice

AEMCO

+966 -11- 21 40 888
marketing@aemco-llc.com
www.aemco-llc.com

جده الدمام الرياض
Riyadh Damman Jeddah



Genuine People
Genuine Spares
Genuine Service