

MULTICUT 400

POWERFUL AND COMPACT FLOOR SAW FOR CHALLENGING BUILDING SITE CONDITIONS

- Compact floor saw with scissor technology
- Drive via hydrostat guarantees smooth and controlled operation of the machine
- Optimum power transfer with high performance V-belts
- Warp-resistant sheet frame construction
- The compact design and balanced chassis permit easy manoeuvring around the construction site
- The low centre of gravity ensures a precise saw cut
- Very good straight cut thanks to the adjustable rear axle
- Electro- hydraulic lowering and raising of the saw blade with a threaded spindle with cutting depth indicator prevents damage to the saw blade
- Height adjustable handles allow for ergonomic operation
- Saw hood front can be raised for intersections
- Rapid changeover from left to right-hand cutting
- Easy access for prevalent maintenances (air filter, battery, oil filter, fuel filter) due to the perfect drive unit position
- Parking brake and neutral (free-wheeling) comes as a standard feature



MULTICUT 400 D
Image shows optional accessories



MULTICUT 400 P
Image shows optional accessories

TECHNICAL DATA	MULTICUT 400 D	MULTICUT 400 P
cutting depth max.	315 mm / 415 mm	315 mm / 415 mm
cutting depth setting	electrohydraulic with depth gauge	electrohydraulic with depth gauge
saw blade Ø max.	800 mm / 1000 mm	800 mm / 1000 mm
arbor size	25.4 mm	25.4 mm
drive motor	Perkins Diesel 3-cyl.	Kohler petrol 2-cyl.
output power max.	18.4 kW / 25 hp	26.1 kW / 35 hp
emission level	stage 5	EU Stage 5 / EPA Phase 3
rated speed / load speed fresh concrete	3040 1/min. / 2800 1/min.	3000 1/min. / 2760 1/min.
rated speed / load speed Ø 600-800	1621 1/min. / 1493 1/min.	1600 1/min. / 1472 1/min.
rated speed / load speed Ø 800-1000	1351 1/min. / 1244 1/min.	1333 1/min. / 1227 1/min.
left and right cut	yes	yes
dimensions (L/W/H)	1300 / 840 / 1690 mm	1300 / 850 / 1200 mm
weight	458 kg	416 kg



FLOOR SAWS	NR.
MULTICUT 400 D without diamond blade, without blade guard (incl. conversion kit)	1210032
MULTICUT 400 P without diamond blade, without blade guard (incl. conversion kit)	1218004

CONVERSION KITS	NR.
Conversion kit for fresh concrete (option 1)	1081255
Conversion kit Ø 600 - 800 mm (option 2)	1210028
Conversion kit Ø 800 - 1000 mm (option 3)	1210121

ACCESSORIES	NR.
Vacuum unit VACUUM-WET 100 P	818167
[1] Blade guard 500 mm, foldable	1081253
[1] Blade guard 600 mm, foldable	1089638
[1] Blade guard 800 mm, foldable	1080927
[1] Blade guard 1000 mm, foldable	1080928
[2] Blade guard 500 mm incl. vacuum shoe	1217058
[2] Blade guard 600 mm incl. vacuum shoe	1217023
[2] Blade guard 800 mm incl. vacuum shoe	1216940
[3] Spot-light LED 12 V	1040256
[4] Warning flasher	816002
Water pump set	813046

TOOL RECOMMENDATION		
Asphalt	→	ASP 201
Asphalt	→	ASP 301
Concrete	→	BSP 102 E
Concrete	→	BSP 203 E
Concrete	→	BSP 202
Concrete	→	BSP 351