MULTICUT 605



POWERFUL FLOOR SAW FOR THE TOUGHEST BUILDING SITE USE

- · Powerful floor saw with scissor technology
- Simple arrangement of the operating elements and a compact multifunctional display facilitate the easy to learn and intuitive operation
- Drive via Hydrostat guarantees a smooth and controlled operation of the machine
- · Optimum power transfer with high performance V-belts
- Shift gearbox with 3 different rpm speeds 950, 1620 and 2450 ¹/min, gearbox (clockwise/counter-clockwise rotation and neutral position), flange spraying system
- · Warp-resistant sheet frame construction
- The compact design and balanced chassis permit easy manoeuvring around the construction site
- · The low centre of gravity ensures a precise saw cut
- · Very good straight cut thanks to the adjustable rear axle
- · Same track of the wheels- large- dimensioned wheels
- · Lifting and lowering of the saw blade is controlled electro-hydraulically
- · Height adjustable handles allow for ergonomic operation
- Rapid changeover from left to right-hand cutting
- · Easy access for prevalent maintenances (air filter, battery, oil filter, fuel filter) due to the perfect drive unit position
- · Parking brake, working hour counter and neutral (free-wheeling) mode come as a standard feature
- Fast and simple v-belt change enables a second rotation speed. Change to other rotation speeds by removing/inserting the saw blade shaft




MULTICUT 605 Image shows optional accessories

TEOURIOAL DATA	ANUTIOUT OF OR
TECHNICAL DATA	MULTICUT 605 SG
cutting depth max.	515 mm
cutting depth setting	electro hydraulic/smoothly adjustable
saw blade Ø max.	1200 mm
arbor size	35 mm (6 x M12 - TK120 mm) - 25,4 mm optional
drive motor	HATZ diesel 4-cylinder
output power max.	55 kW / 74.8 hp
emission level	stage 5 (incl. diesel particulate filter)
cutting gear forwards	hydrostatic stepless 0-50 m/min
cutting gear reverse	hydrostatic stepless 0-25 m/min
saw blade speed	950 / 1620 / 2450 ¹/min.
left and right cut	yes
dimensions (L/W/H)	1995 / 1030 / 1720 mm
weight	1070 kg
-	















[4] Warning flasher

FLOOR SAWS	NR.
MULTICUT 605 SG 35/25,4 mm without diamond blade, without blade guard	1063648
ACCESSORIES	
[1] Vacuum unit VACUUM-WET 100 P	818167
Blade guard 800 mm, foldable	1031207
Blade guard 1000 mm, foldable	1031208
Blade guard 1200 mm, foldable	1031209
[2] Blade guard 500 mm incl. vacuum shoe	1004709
[2] Blade guard 600 mm incl. vacuum shoe	816155
[2] Blade guard 800 mm incl. vacuum shoe	816187
[2] Blade guard 1000 mm incl. vacuum shoe	1079852
[3] Spot-light LED 12 V	1040256
[4] Warning flasher	816002
Water pump set incl. water filter	813046
Adapter kit - shaft 25,4 mm for 6-hole flange	1018697
Weight plates set incl. bracket - front attachment (8 weight plates, 10 kg each) *	1218377

Asphalt

Asphalt

Asphalt

Concrete

Concrete

ASP 602

ASP 703

ASP 751

BSP 451

BSP 501

 \rightarrow

 \rightarrow

 \rightarrow

^{*} Further weight plates sets in the spare parts list