FBM



THE IDEAL MACHINES FOR CLEANING JOINTS

- · Optimum weight distribution for rapid repositioning and set-up
- Height adjustability and positioning of handlebars for a perfect view of the tool
- Continuous oil supply extends the service life of the horizontally mounted motor - this also increases the air filter maintenance intervals
- · The adjustable front axle guarantees uniform processing of the joint
- Standard with parking brake and threaded spindle for setting the working depth
- · An optional LED working light, in combination with the generator kit, is recommended for use at night or in a tunnel
- · Eye hooks for simple unloading and transportation
- · Detachable brush guard with adjustable deflectors
- · Waste collector basket to catch debris from joint (optional)
- The tool cutting direction is against the working direction so dirt kept out of the fresh cut area



TECHNICAL DATA	FBM 300 P	FBM 300 D
brush width	6-18 mm	6-18 mm
brush depth	60 mm	60 mm
brush Ø	300 mm	300 mm
brush holder	20.0 mm / 25.4 mm	20.0 mm / 25.4 mm
fuel	petrol	diesel
output power max.	8.7 kW, 11.7 hp	7.3 kW, 9.8 hp
emission level	-	EPA Tier IV Final
speed	2800 ¹/min.	2800 ¹ /min.
dimensions (L/W/H)	1300/ 650/930 mm	1300/ 650/930 mm
weight	115 kg	137 kg









[1] Steering wheel mounting kit

[2] Waste disposal box

[3] Alternator kit

[4] Spot-light



[5] Round brush

JOINT BRUSHING			NR.
FBM 300 P joint brushing mach	nine without tools		1004145
FBM 300 D joint brushing mac	nine without tools		1005367
ACCESSORIES			NR.
[1] Steering wheel mounting	819555		
[2] Waste disposal box			819561
[3] Alternator kit			1004326
[4] Spot-light LED 12 V			1040256
TOOLS			NR.
[5] Round brush Ø 300 mm/20	799781		
[5] Round brush Ø 300 mm/20	799750		
[5] Round brush Ø 300 mm/20	799751		
[5] Round brush Ø 300 mm/20	799752		
[5] Round brush Ø 300 mm/20	799786		
TOOL RECOMMENDATION			
Asphalt/Concrete	\rightarrow	RSW 10	
Asphalt	\rightarrow	AASW 11	
Concrete	\rightarrow	BASW 11	