

THE COMPACT DIAMOND CORE DRILLING MACHINES FOR WET AND DRY DRILLING

- Compact, lightweight and ergonomic design
- 3 speed gear box allows optimum speed selection
- Simple, controlled operation during hand-guided core drilling using universal clamping handle

MULTI-TRONIC

- Overload protection for the highest possible operating comfort and long service life
- Maximum safety due to electronic and mechanical overload coupling as well as additional thermal overload protection



CDM 20 P



CDM 20 S

| TECHNICAL DATA | CDM 20 P | CDM 20 S |
|----------------------------|----------------------|----------------------|
| rated power | 2000 W | 2000 W |
| output power | 1375 W | 1375 W |
| voltage | 230 V/50-60 Hz | 230 V/50-60 Hz |
| rated current | 9.5 A | 9.5 A |
| speed without load | 670/1450/2770 1/min. | 670/1450/2770 1/min. |
| speed fully load | 450/1050/2000 1/min. | 450/1050/2000 1/min. |
| core drill Ø masonry max. | 200 mm | 200 mm |
| core drill Ø concrete max. | 150 mm | 150 mm |
| core bit connection | 1 1/4" UNC | 1 1/4" UNC |
| clamping collar Ø | 60 mm | 60 mm |
| dimensions (L/W/H) | 468/106/297 mm | 564/106/164 mm |
| weight | 7.5 kg | 7.5 kg |



[1] Antifriction washer



[2] Centre spike



CDM 20 P incl. carry case

CORE DRILL MOTORS 230 V

NR.

CDM 20 P wet/dry, incl. carry case

1004139

CDM 20 S wet/dry, incl. carry case

1004304

ACCESSORIES

NR.

[1] antifriction washer (brass)

823520

[2] centre spike 190 - 250mm

700353

[2] centre spike 230 - 350 mm

700354

[2] centre spike 360 - 480 mm

700355

adapter cable 2m plug Schuko | coupl. CEE 3-pin 16 A

822312

adapter cable 2m plug CEE 3-pin 16 A | coupl. Schuko

822310